NSN 5905-00-928-9056

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-928-9056 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 2.850 inches and 2.910 inches **Body Diameter:** 1.437 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** Between 0.850 inches and 0.910 inches **Mounting Bushing Length:** 0.380 inches **Body Length:** 2.000 inches **Overall Diameter:** 1.437 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve Switch Type: Rotary **Switch Voltage Rating In Volts:** 28.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 351.0 and 353.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Maximum Stop Torque:** 80.00 inch-ounces **Shaft End Play:** 0.01000 inches

Shaft Runout: 0.020 inches

NSN 5905-00-928-9056

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:

0.010 inches

Mechanical Backlash In Deg Angular Rotation:

0.25

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, double throw, three positions maintained

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

20.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 350.0 and 354.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-500.0/+500.0 ohms single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Tap Location From Ccw Terminal Per Section In Ohms:

10000.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

NSN 5905-00-928-9056

Precision Wire Wound Variable Resistor - Page 3 of 3



Switch Current Type And Rating In Amps:
0.100 dc
Special Features:
W/special features for proper functioning of the item
Terminal Type And Quantity:
4 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0