NSN 5905-00-929-0482

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-929-0482 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.427 inches **Terminal Length:** 0.188 inches **Body Diameter:** 0.510 inches **Body Length:** 0.235 inches **Overall Diameter:** 0.510 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 310.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 15.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 5.0 kilohms single section **Rotary Actuator Travel In Angular Deg:**

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

NSN 5905-00-929-0482

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -70.0/+70.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A002a0