NSN 5905-00-929-2384

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-929-2384

Onesting Occupation
Section Quantity:
Body Style:
Rectangular
Reliability Indicator:
Not established
Shaft Diameter:
0.125 inches
Shaft Length:
0.416 inches
Body Length:
1.750 inches
Body Width:
1.000 inches
Body Height:
2.500 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
1.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section

NSN 5905-00-929-2384

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0