## NSN 5905-00-929-3067

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-929-3067 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.000 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.375 inches **Overall Diameter:** 1.437 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 100.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Function Characteristic Per Section:** Single section linear **Terminal Type And Quantity:** 3 tab, solder lug

Shelf Life: N/a

## NSN 5905-00-929-3067

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0