Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-930-1336

### Section Quantity:

1

Body Style:

Rectangular

### **Reliability Indicator:**

Not established

### Shaft Diameter:

0.110 inches

#### Shaft Length:

0.120 inches

#### **Body Length:**

0.750 inches

### **Body Width:**

0.160 inches

### **Body Height:**

### 0.310 inches

Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

### **Terminal Location:**

Lower adjacent side single row

### Mounting Method:

Terminal

### **Features Provided:**

Nonmetallic shaft

### **Electrical Resistance Per Section:**

100.0 kilohms single section

### **Rotary Actuator Travel In Angular Deg:**

5400.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-400.0/+400.0 single section

## Power Dissipation Rating Per Section In Watts:

0.2 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

# Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

### Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0