

View Online at <https://aerobasegroup.com/nsn/5905-00-930-2839>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.9683 inches and 0.9689 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

1.762 inches

**Undercut Diameter:**

Between 0.950 inches and 0.980 inches

**Undercut Width:**

Between 0.0420 inches and 0.0820 inches

**Body Diameter:**

Between 1.060 inches and 1.064 inches

**Shaft Diameter:**

0.120 inches

**Shaft Length:**

Between 0.414 inches and 0.446 inches

**Body Length:**

1.270 inches

**Overall Diameter:**

1.400 inches

**Mounting Lip Diameter:**

Between 1.0420 inches and 1.0820 inches

**Mounting Lip Depth:**

Between 0.0420 inches and 0.0820 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

351.5

**Maximum Starting Torque:**

3.00 inch-ounces

**Maximum Running Torque:**

3.00 inch-ounces

**Shaft End Play:**

0.003 inches

**Pilot Diameter Runout:**

0.001 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

1.0 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.30/+0.30 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-300.0/+300.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Function Conformity Per Section:**

All sections independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0