NSN 5905-00-931-0048

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-931-0048 **Section Quantity:** 2 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.086 inches **Body Length:** 1.250 inches **Body Width:** 0.500 inches **Body Height:** 0.312 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 50.0 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 all sections Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 all sections **Power Dissipation Rating Per Section In Watts:** 0.5 free air all sections **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 all sections **Actuator Travel Control Feature:**

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

NSN 5905-00-931-0048

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0