NSN 5905-00-931-0099

Section Quantity:

Cylindrical bushing mounted

Body Style:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-931-0099

Reliability Indicator:
Not established
Body Diameter:
1.062 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Body Length:
0.625 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
050.0
350.0
Maximum Stop Torque:
Maximum Stop Torque:
Maximum Stop Torque: 0.50 inch-ounces
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play:
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout:
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout: 0.002 inches
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout: 0.002 inches Lateral Runout:
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout: 0.002 inches Lateral Runout: 0.002 inches
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout: 0.002 inches Lateral Runout: 0.002 inches Pilot Diameter Runout:
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout: 0.002 inches Lateral Runout: 0.002 inches Pilot Diameter Runout: 0.0015 inches
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout: 0.002 inches Lateral Runout: 0.002 inches Pilot Diameter Runout: 0.0015 inches Shaft Radial Play:
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout: 0.002 inches Lateral Runout: 0.002 inches Pilot Diameter Runout: 0.0015 inches Shaft Radial Play: 0.002 inches
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout: 0.002 inches Lateral Runout: 0.002 inches Pilot Diameter Runout: 0.0015 inches Shaft Radial Play: 0.002 inches Terminal Location:
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout: 0.002 inches Lateral Runout: 0.002 inches Pilot Diameter Runout: 0.0015 inches Shaft Radial Play: 0.002 inches Terminal Location: Radially positioned over less than half the circumference Mounting Method:
Maximum Stop Torque: 0.50 inch-ounces Shaft End Play: 0.0025 inches Shaft Runout: 0.002 inches Lateral Runout: 0.002 inches Pilot Diameter Runout: 0.0015 inches Shaft Radial Play: 0.002 inches Terminal Location: Radially positioned over less than half the circumference

NSN 5905-00-931-0099 Precision Wire Wound Variable Resistor - Page 2 of 2

