

NSN 5905-00-931-0127 Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-931-0127 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.422 inches **Body Length:** Between 0.769 inches and 0.801 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** Between 235.0 and 245.0 **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 8.00 inch-ounces **Fragility Factor:** Moderately rugged **Terminal Location:** Front end **Mounting Method:** Flange **Features Provided:** Grounded contact arm **Cubic Measure:** 0.112 cubic inches **Electrical Resistance Per Section:**

1.2 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 235.0 and 245.0

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Screwdriver slot adjustment

Terminal Type And Quantity:

1 tab, solder lug

NSN 5905-00-931-0127

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0