Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-931-0127 Section Quantity: 1 **Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.422 inches **Body Length:** Between 0.769 inches and 0.801 inches Actuator Type: Flush drive with slot-hole Effective Electrical Rotation In Deg Angular Rotation: Between 235.0 and 245.0 Maximum Starting Torque: 8.00 inch-ounces Maximum Running Torque: 8.00 inch-ounces **Fragility Factor:** Moderately rugged **Terminal Location:** Front end **Mounting Method:** Flange **Features Provided:** Grounded contact arm **Cubic Measure:** 0.112 cubic inches **Electrical Resistance Per Section:** 1.2 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 235.0 and 245.0 **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Standard Taper Curve Per Section: A single section **Special Features:** Screwdriver slot adjustment **Terminal Type And Quantity:** 

1 tab, solder lug



Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0