Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-931-1204

## Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.258 inches and 1.342 inches **Terminal Length:** Between 6.000 inches and 8.000 inches **Overall Height:** Between 0.305 inches and 0.360 inches **Overall Width:** Between 0.243 inches and 0.300 inches **Mounting Hole Diameter:** Between 0.087 inches and 0.100 inches Shaft Diameter: 0.125 inches Shaft Length: Between 0.040 inches and 0.060 inches **Body Length:** Between 1.218 inches and 1.282 inches **Body Width:** Between 0.243 inches and 0.300 inches **Body Height:** Between 0.305 inches and 0.360 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Running Torque:

8.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

Between 0.985 inches and 1.015 inches

## **Mounting Facility Quantity:**

2

**Terminal Location:** All adjacent sides from adjacent control **Mounting Method:** Unthreaded hole

**Electrical Resistance Per Section:** 

2.500 kilohms single section

Precision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

9000.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

---

Fiig:

A002a0