NSN 5905-00-931-1204

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-931-1204

view Online at https://aerobasegroup.com/nsn/5905-00-93
Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
Between 1.258 inches and 1.342 inches
Terminal Length:
Between 6.000 inches and 8.000 inches
Overall Height:
Between 0.305 inches and 0.360 inches
Overall Width:
Between 0.243 inches and 0.300 inches
Mounting Hole Diameter:
Between 0.087 inches and 0.100 inches
Shaft Diameter:
0.125 inches
Shaft Length:
Between 0.040 inches and 0.060 inches
Body Length:
Between 1.218 inches and 1.282 inches
Body Width:
Between 0.243 inches and 0.300 inches
Body Height:
Between 0.305 inches and 0.360 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Running Torque:
8.00 inch-ounces
Lateral Distance Between Mounting Hole Centers:
Between 0.985 inches and 1.015 inches
Mounting Facility Quantity:
2
Terminal Location:
All adjacent sides from adjacent control
Mounting Method:
Unthreaded hole

2.500 kilohms single section

Electrical Resistance Per Section:

NSN 5905-00-931-1204

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -250.0/+250.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:** No