NSN 5905-00-931-1738

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-931-1738

Electrical Resistance: 10.000 kilohms Resistance Tolerance in Percent: 10.000 41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 1275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0*275.0 Inclosure Method: Encepsulated Terminal Type: Wife lead Reliability Indicator: Not established 30dy Diameter: 10.187 inches 30dy Length: 10.560 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Xaxial terminal each end Test Data Document: 11349*—Init 26% specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Via Jint Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1275.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 1275.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.04/275.0 Inclosure Method: 150.04/275.0 Inclosure	-30.0/+30.0
Resistance Tolerance in Percent: 1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0+275.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established 300dy Diameter: 10.187 inches 300dy Length: 10.560 inches Power Dissipation Rating in Watts: 10.3000 free air Style Designator: Axial terminal each end Test Data Document: 10.149 mill:26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 25.046 Life: 26.04 inches 26.05 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). 26.16 Life: 26.16 Messure: 27.16 Messure: 28.17 Messure: 29.18 Messure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Tempurature Method: Tem	10.000 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0+2/75.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Vot established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 93/49-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Juit Of Measure: - Demilitarization: Via	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: D.187 inches Body Diameter: D.187 inches Power Dissipation Rating In Watts: By Designator: Axial terminal each end Test Data Document: By Designation: By Designation: By Designation (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Ditt Of Measure: Demilitarization: No	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: D. 187 inches Body Length: D. 560 inches Power Dissipation Rating In Watts: Bodo free air Style Designator: Axial terminal each end Test Data Document: Bat 349-milr 26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similiar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Ditt Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Permpurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Perminal Type: Write lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: B.000 free air Style Designator: Existing Land Document: B1349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Juit Of Measure: Demilitarization: No Perminal Communication of Tempurature Coefficient In Deg Celsius: Style Designator Style Designator Style Designator Existing Land December 11 Style Designator S	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 nclosure Method: ncapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 8.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No Figig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: D.187 inches Body Diameter: D.187 inches Power Dissipation Rating In Watts: 8,000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milit26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Shelf Life: Wa Juit Of Measure: Demilitarization: No Filig:	275.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: D. 187 inches Body Length: D. 580 inches Power Dissipation Rating In Watts: Body Designator: Axial terminal each end Fest Data Document: Bital D	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 8.000 free air Style Designator: Axial terminal each end Ferst Data Document: 181349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Pilig:	-55.0/+275.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 8.000 free air Style Designator: Avial terminal each end Ferst Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Perilig:	Inclosure Method:
Action of Measure: Action	Encapsulated
Reliability Indicator: Not established Body Diameter: D. 187 inches Body Length: D. 560 inches Power Dissipation Rating In Watts: B. 300 free air Style Designator: Axial terminal each end Fest Data Document: B1349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: - Demilitarization: No	Terminal Type:
Note established Body Diameter: D.187 inches Body Length: D.560 inches Power Dissipation Rating In Watts: B.000 free air Style Designator: Avail terminal each end Fest Data Document: B.1349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Bhelf Life: N/a Unit Of Measure: Demilitarization: No	Wire lead
30 dy Length: 0.187 inches 30 dy Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Reliability Indicator:
20.187 inches 30 dy Length: 20.560 inches 20 wer Dissipation Rating In Watts: 20.000 free air 20 Style Designator: Axial terminal each end 20 Fest Data Document: 20 349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 20 excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 20 Shelf Life: 20 Wa 20 Juit Of Measure: 20 Demilitarization: 20 No	Not established
Body Length: 0.560 inches Power Dissipation Rating In Watts: 8.000 free air Style Designator: Axial terminal each end Fest Data Document: 8.1349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No	Body Diameter:
Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Junit Of Measure: Demilitarization: No Single Power Dissipation Rating In Watts: Style Designator: Demilitarization: No Single Power Dissipation Rating In Watts: Style Designator: Style Designator: Axial terminal each end Fest Data Document: Axial terminal each end Fest	0.187 inches
Power Dissipation Rating In Watts: 8.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filig:	0.560 inches
Style Designator: Axial terminal each end Fest Data Document: 31349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	3.000 free air
Fest Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 8helf Life: N/a Jnit Of Measure: - Demilitarization: No Fig:	Style Designator:
31349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Jnit Of Measure: - Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization: No -	Shelf Life:
- Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
	Fiig:
\ 001a0	A001a0