

View Online at <https://aerobasegroup.com/nsn/5905-00-931-3212>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

Between 1.300 inches and 1.340 inches

Terminal Length:

6.000 inches

Overall Height:

Between 0.300 inches and 0.330 inches

Overall Width:

Between 0.180 inches and 0.200 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

Between 0.100 inches and 0.130 inches

Shaft Length:

Between 0.060 inches and 0.080 inches

Body Length:

Between 1.240 inches and 1.260 inches

Body Width:

Between 0.180 inches and 0.200 inches

Body Height:

Between 0.300 inches and 0.330 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 6120.0 and 9720.0

Maximum Starting Torque:

8.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 6120.0 and 9720.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 wire lead

Specification Data:

81349-mil-r-22097/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0