NSN 5905-00-931-3806

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-931-3806 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.300 inches **Overall Width:** Between 0.283 inches and 0.297 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** Between 0.040 inches and 0.060 inches **Body Length:** 1.250 inches **Body Width:** Between 0.283 inches and 0.297 inches **Body Height:** 0.344 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 8640.0 **Maximum Starting Torque:** 8.00 inch-ounces **Shaft End Play:** 0.00020 inches **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity: Terminal Location:** Lower adjacent side single row

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

1.0 megohms single section

NSN 5905-00-931-3806

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9720.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: