NSN 5905-00-931-5675

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-931-5675

-15.0/+15.0 Electrical Resistance: 800.000 ohms Resistance Tolerance In Percent: -0.020/+0.020 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 inches Power Dissipation Rating In Watts: 1.000 inches Style Designator: Axial terminal each end Test Style Designator: Axial terminal each end Test Sea Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc., excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N\a Unit of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -0.020/-0.020 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Body Length: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 0.4655-36-269703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure:	-15.0/+15.0
Resistance Tolerance In Percent: -0.020/+0.020 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justiffication: Test Style Designator: Axial terminal each end Test Data Document: 04665-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-60000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	600.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating in Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: O4655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-0.020/+0.020
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	145.0
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+125.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hermetically sealed
Reliability Indicator: Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Not established Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter: 0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 0.4655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.500 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Length: 1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
1.000 inches Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.500 inches
Power Dissipation Rating In Watts: 1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
1.000 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.000 inches
Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.000 free air
Style Designator: Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Criticality Code Justification:
Axial terminal each end Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test
Test Data Document: 04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	04655-36-268703-6000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer
N/a Unit Of Measure: Demilitarization: No Fiig:	drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0