Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-931-7730

## Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

### **Overall Length:**

1.060 inches

#### Terminal Length:

0.250 inches

Shaft Diameter:

0.093 inches

Shaft Length:

0.060 inches

Body Length:

# 1.000 inches

**Body Width:** 

0.280 inches

#### **Body Height:**

0.360 inches

#### Shaft Style:

Round, slotted

## Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

#### Maximum Starting Torque:

5.00 inch-ounces

#### Maximum Running Torque:

5.00 inch-ounces

#### Center To Center Distance Between Terminals:

0.500 inches

#### **Terminal Location:**

Longitudinally positioned on the circumference

#### Mounting Method:

Terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

### **Electrical Resistance Per Section:**

20.0 kilohms single section

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.2 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0