Nonprecision Wire Wound Variable Resistor - Page 1 of 2



NSN 5905-00-932-1432 View Online at https://aerobasegroup.com/nsn/5905-00-932-1432 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.937 inches **Shaft Diameter:** 0.248 inches **Shaft Length:** 0.687 inches **Body Length:** 1.374 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

1

Terminal Location:

Lower adjacent side single row

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

NSN 5905-00-932-1432

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0