

View Online at <https://aerobasegroup.com/nsn/5905-00-932-2743>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.750 inches

First Flat Length:

0.625 inches

Flat Height:

0.216 inches

Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.375 inches

Mounting Bushing Length:

0.500 inches

Body Length:

1.266 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing w/shaft seal

Electrical Resistance Per Section:

100.000 kilohms all sections

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+4.5 -55 degrees celsius all sections and +0.0/+2.5 -25 degrees celsius all sections and +0.0/+1.5 0 degrees celsius all sections and -1.5/+1.5 85 degrees celsius all sections and +0.0/+3.5 120 degrees celsius all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

2.25 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0