NSN 5905-00-932-2971

Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-932-2971



Section Quantity: Body Style: Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.452 inches **Body Diameter:** 3.190 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** Between 0.578 inches and 0.672 inches **Mounting Bushing Length:** Between 0.453 inches and 0.547 inches **Body Length:** 1.780 inches **Overall Diameter:** 3.785 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 48.00 inch-ounces **Maximum Stop Torque:** 240.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** Between 0.485 inches and 0.515 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity:**

Terminal Location:

Radially positioned over less than half the circumference

NSN 5905-00-932-2971

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Mounting Method: |
|--|
| Locking bushing |
| Electrical Resistance Per Section: |
| 2.0 ohms single section |
| Rotary Actuator Travel In Angular Deg: |
| Between 295.0 and 315.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 340.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 100.0 heat sink single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 25.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Specification Data: |
| 81349-mil-r-22/8 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |