Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-932-4590

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.094 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.812 inches

### Mounting Bushing Length:

0.375 inches

#### Body Length:

### 0.562 inches

Shaft Style:

Round

Actuator Type:

Single shaft

### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

10.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

Between 330.0 and 340.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

# Actuator Travel Control Feature:

Stops



### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0