NSN 5905-00-932-4986

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-932-4986

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 0.62450 inches and 0.62500 inches
Pilot Length:
Between 0.05700 inches and 0.06700 inches
Overall Length:
1.955 inches
Undercut Diameter:
0.781 inches
Undercut Width:
Between 0.05700 inches and 0.06700 inches
Body Diameter:
Between 0.859 inches and 0.891 inches
Shaft Diameter:
0.125 inches
Shaft Length:
Between 0.344 inches and 0.406 inches
Body Length:
1.580 inches
Mounting Lip Diameter:
Between 0.85900 inches and 0.89100 inches
Mounting Lip Depth:
Between 0.05700 inches and 0.06700 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 3600.0 and 3610.0
Maximum Starting Torque:
0.40 inch-ounces
Maximum Running Torque:
0.30 inch-ounces
Maximum Stop Torque:
00 00 inch aurage

96.00 inch-ounces

NSN 5905-00-932-4986

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.00300 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
2.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.20/+0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-932-4986

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0