## NSN 5905-00-932-6967

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-932-6967 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.422 inches **Terminal Length:** Between 0.177 inches and 0.197 inches **Body Diameter:** Between 0.490 inches and 0.510 inches **Body Length:** Between 0.225 inches and 0.245 inches **Overall Diameter:** Between 0.490 inches and 0.512 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Starting Torque:** 7.50 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 500.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 320.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.095 inches and 0.105 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section

**Actuator Travel Control Feature:** Stops

## NSN 5905-00-932-6967

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature (	Coefficient Of	<b>Resistance W</b>	Vire Per Se	ection In P	pm Per De	g Celsius:
---------------	----------------	---------------------	-------------	-------------	-----------	------------

-70.0/+70.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0