NSN 5905-00-932-8332

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-932-8332 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Pilot Diameter:** 1.31250 inches Pilot Length: 0.06200 inches **Overall Length:** 3.062 inches **Undercut Width:** 0.07300 inches **Body Diameter:** 1.437 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.938 inches **Body Length:** 2.062 inches **Overall Diameter:** 1.718 inches **Mounting Lip Diameter:** 1.43700 inches **Mounting Lip Depth:** 0.09300 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Maximum Starting Torque:** 1.30 inch-ounces **Shaft End Play:** 0.00200 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.001 inches **Pilot Diameter Runout:**

0.00100 inches

NSN 5905-00-932-8332

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
50.000 percent, rated amperes c and better industrial clears
Rotary Actuator Travel In Angular Deg:
360.0
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 3rd section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
20.0 single section
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0