Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-933-1132

Section Quantity: 1 Body Style: Cylindrical bushing mounted Overall Length: 3.010 inches Body Diameter: Between 1.750 inches and 1.880 inches Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

0.440 inches

Mounting Bushing Length:

Between 0.340 inches and 0.420 inches

Body Length:

1.750 inches

Overall Diameter:

Between 1.750 inches and 1.880 inches

Shaft Style:

Round

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Grounded contact arm

Electrical Resistance Per Section:

100.000 ohms single section

Fixed Tap Quantity Per Section:

2 single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 1st section

Test Data Document:

81349-milr22b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0