NSN 5905-00-933-3471

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-933-3471 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.469 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Radius:** 0.245 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 500.0 ohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:**

00.0/.00.0 : 1 ::

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

NSN 5905-00-933-3471

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
F single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0