

View Online at <https://aerobasegroup.com/nsn/5905-00-933-6539>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.6250 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

2.040 inches

**Undercut Diameter:**

0.750 inches

**Undercut Width:**

0.0630 inches

**Body Diameter:**

0.875 inches

**Shaft Diameter:**

0.1248 inches

**Shaft Length:**

0.376 inches

**Body Length:**

1.536 inches

**Overall Diameter:**

1.084 inches

**Mounting Lip Diameter:**

0.8750 inches

**Mounting Lip Depth:**

0.0630 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

0.70 inch-ounces

**Maximum Running Torque:**

0.60 inch-ounces

**Maximum Stop Torque:**

50.00 inch-ounces

**Shaft Runout:**

0.003 inches

**Mechanical Backlash In Deg Angular Rotation:**

1.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

1.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.25/+0.25 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-2.5/+2.5 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0