

View Online at <https://aerobasegroup.com/nsn/5905-00-933-9206>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

Between 2.960 inches and 3.060 inches

**Terminal Length:**

0.380 inches

**Body Diameter:**

Between 1.750 inches and 1.888 inches

**Shaft Diameter:**

Between 0.248 inches and 0.251 inches

**Shaft Length:**

0.440 inches

**Mounting Bushing Length:**

Between 0.340 inches and 0.420 inches

**Body Length:**

1.750 inches

**Overall Diameter:**

Between 1.750 inches and 1.888 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 3 oclock

**Nonturn Device Radius:**

Between 0.490 inches and 0.510 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Locking bushing

**Electrical Resistance Per Section:**

100.000 ohms single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

40.0 single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 1st section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Cable 16.38 in. Min, 17.38 in. Maximum lg soldered to each terminal

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0