

View Online at <https://aerobasegroup.com/nsn/5905-00-933-9206>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

Between 2.960 inches and 3.060 inches

Terminal Length:

0.380 inches

Body Diameter:

Between 1.750 inches and 1.888 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

0.440 inches

Mounting Bushing Length:

Between 0.340 inches and 0.420 inches

Body Length:

1.750 inches

Overall Diameter:

Between 1.750 inches and 1.888 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

Between 0.490 inches and 0.510 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

100.000 ohms single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

40.0 single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 1st section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Cable 16.38 in. Min, 17.38 in. Maximum lg soldered to each terminal

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0