Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-934-2844

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.891 inches

Body Diameter:

1.000 inches

Shaft Diameter:

Between 0.249 inches and 0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.500 inches

Body Length:

1.891 inches

Overall Diameter:

1.000 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

5400.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.375 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference



Mounting Method: Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 5.0 kilohms single section **Function Conformity Tolerance Per Section:** -0.05/+0.05 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 100.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Test Data Document:** 12464-b75f0050-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** Shelf Life: Unit Of Measure: **Demilitarization:**

3 turret

N/a

--

No Fiig: A002a0