## NSN 5905-00-935-1142

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-935-1142

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:                |
|--|
| -50.0/+50.0  |
| Electrical Resistance:   |
| 1.430 ohms   |
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Heat Sink Material:  |
| Aluminum alloy   |
| Heat Sink Length:  |
| 6.000 inches   |
| Heat Sink Width:   |
| 4.000 inches   |
| Heat Sink Height:  |
| 2.000 inches   |
| Heat Sink Thickness:   |
| 0.040 inches   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:                      |
| 25.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:              |
| 125.0  |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Eyelet   |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:                                   |
| 1.000  |
| Terminal Length:   |
| 0.266 inches   |
| Body Length:   |
| 0.600 inches   |
| Body Width:  |
| 0.334 inches   |
| Body Height:   |
| 0.320 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.444 inches   |
| Power Dissipation Rating In Watts:   |
| 5.000 heat sink  |
| Mounting Hole Size:  |
| 0.093 inches   |

## NSN 5905-00-935-1142

Inductive Wire Wound Fixed Resistor - Page 2 of 2



| Style Designator:  |
|--------------------|
| Axial terminal (s) |
| Shelf Life:        |
| N/a                |
| Unit Of Measure:   |
|                    |
| Demilitarization:  |
| No                 |
| Fiig:              |

A001a0