## NSN 5905-00-935-6954

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-935-6954 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.050 inches **Terminal Length:** 6.000 inches **Overall Height:** 0.315 inches **Overall Width:** 0.180 inches **Mounting Hole Diameter:** 0.088 inches **Shaft Diameter:** 0.050 inches **Shaft Length:** 0.050 inches **Body Length:** 1.000 inches **Body Width:** 0.180 inches **Body Height:** 0.315 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** 0.750 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Features Provided:** 

Nonmetallic shaft **Electrical Resistance Per Section:** 

50.000 ohms single section

## NSN 5905-00-935-6954

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0