Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-935-8593

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

2.332 inches

### Terminal Length:

0.580 inches

**Body Diameter:** 

1.680 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

### Shaft Length:

Between 0.828 inches and 0.922 inches

### Mounting Bushing Length:

0.375 inches

### **Body Length:**

1.410 inches

# **Overall Diameter:**

2.260 inches

# Shaft Style:

Round, slotted

## Contact Arm Electrical Off Position:

Fully cw

### Actuator Type:

Single shaft

### Maximum Starting Torque:

40.00 inch-ounces

### Maximum Stop Torque:

240.00 inch-ounces

### **Nonturn Device Location:**

At 12 oclock

### Nonturn Device Radius:

Between 0.485 inches and 0.515 inches

# Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0



**Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 75.000 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 275.0 and 305.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section **Power Dissipation Rating Per Section In Watts:** 25.0 heat sink single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-milr22-3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig:

A002a0