# NSN 5905-00-936-1622

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-936-1622

Section	Quantity:
---------	-----------

1

#### **Body Style:**

Rectangular w/mounting holes/slots

#### **Reliability Indicator:**

Not established

#### **Overall Length:**

Between 1.265 inches and 1.359 inches

#### **Terminal Length:**

Between 0.484 inches and 0.516 inches

#### **Overall Height:**

Between 0.296 inches and 0.328 inches

#### **Overall Width:**

Between 0.270 inches and 0.290 inches

#### **Mounting Hole Diameter:**

0.088 inches

#### **Shaft Diameter:**

Between 0.078 inches and 0.172 inches

## **Shaft Length:**

Between 0.015 inches and 0.119 inches

## **Body Length:**

Between 1.234 inches and 1.266 inches

#### **Body Width:**

Between 0.270 inches and 0.290 inches

#### **Body Height:**

Between 0.265 inches and 0.359 inches

# Shaft Style:

Round, slotted

# **Actuator Type:**

Single shaft

#### **Effective Electrical Rotation In Deg Angular Rotation:**

7920.0

#### **Maximum Starting Torque:**

5.00 inch-ounces

#### **Center To Center Distance Between Terminals:**

Between 0.690 inches and 0.710 inches

#### **Lateral Distance Between Mounting Hole Centers:**

Between 0.995 inches and 1.005 inches

# **Mounting Facility Quantity:**

2

#### **Terminal Location:**

Lower adjacent side single row

# NSN 5905-00-936-1622

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
2.200 megohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.290 inches and 0.310 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-500.0/+300.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0