NSN 5905-00-936-3792

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-936-3792

Section Quantity: Body Style: Rectangular **Reliability Indicator:** Not established **Terminal Length:** Between 0.490 inches and 0.510 inches **Body Length:** Between 0.546 inches and 0.578 inches **Body Width:** Between 0.296 inches and 0.328 inches **Body Height:** Between 0.490 inches and 0.510 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 310.0 **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Lower adjacent side two rows **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 0.110 inches **Electrical Resistance Per Section:** 500.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 320.0 Center To Center Distance Between Center Terminal And Outside Terminal: Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:**

Stops

NSN 5905-00-936-3792

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
50.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	