

View Online at https://aerobasegroup.com/nsn/5905-00-936-4104

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.297 inches and 1.327 inches **Terminal Length:** Between 0.435 inches and 0.515 inches **Overall Height:** Between 0.795 inches and 0.825 inches **Overall Width:** Between 0.270 inches and 0.290 inches **Mounting Hole Diameter:** 0.088 inches Shaft Diameter: Between 0.110 inches and 0.140 inches Shaft Length: Between 0.047 inches and 0.077 inches **Body Length:** Between 1.235 inches and 1.265 inches **Body Width:** Between 0.270 inches and 0.290 inches **Body Height:** Between 0.297 inches and 0.327 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 Maximum Starting Torque: 5.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.690 inches and 0.710 inches Lateral Distance Between Mounting Hole Centers: Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:**

Lower adjacent side single row



Center To Center Distance Between Terminal Rows: 0.100 inches Electrical Resistance Per Section: 500.000 kilohms single section Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.290 inches and 0.310 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Unthro	ting Method: eaded hole
0.100 inches Electrical Resistance Per Section: 500.000 kilohms single section Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.290 inches and 0.310 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Electrical Resistance Per Section: 500.000 kilohms single section Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.290 inches and 0.310 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:		
500.000 kilohms single section Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.290 inches and 0.310 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.290 inches and 0.310 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:		
9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.290 inches and 0.310 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		-
Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.290 inches and 0.310 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:		
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
175.0 single section Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Betwe	en 0.290 inches and 0.310 inches
Power Dissipation Rating Per Section In Watts: 0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Ambie	ent Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
0.5 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Power	Dissipation Rating Per Section In Watts:
-10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.5 fre	e air single section
Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Resist	tance Tolerance Per Section In Percent:
Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-10.0/+	+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Actuat	tor Travel Control Feature:
70.0 single section Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Stops	
Special Features: Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Ambie	ent Tempurature In Deg Celsius Per Section At Full Rated Power:
Pin diameter 0.028 in porm 0.005 in, terminals gold plated Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	70.0 si	ingle section
Terminal Type And Quantity: 3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specia	al Features:
3 pin Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Pin dia	ameter 0.028 in porm 0.005 in, terminals gold plated
Reference Number Differentiating Characteristics: Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Termi	nal Type And Quantity:
Navord od42046 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3 pin	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Refere	ence Number Differentiating Characteristics:
N/a Unit Of Measure: Demilitarization: No Fiig:		
Unit Of Measure: Demilitarization: No Fiig:		Life:
 Demilitarization: No Fiig:		
No Fiig:	Unit O)f Measure:
No Fiig:		
Fiig:		itarization:
-		
A002a0	-	