

View Online at <https://aerobasegroup.com/nsn/5905-00-936-5950>

Section Quantity:

3

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.8750 inches

Pilot Length:

Between 0.0550 inches and 0.0650 inches

Overall Length:

Between 2.634 inches and 2.696 inches

Undercut Diameter:

1.875 inches

Undercut Width:

0.0600 inches

Body Diameter:

Between 1.995 inches and 2.005 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.719 inches and 2.696 inches

Body Length:

1.915 inches

Overall Diameter:

2.500 inches

Mounting Lip Diameter:

Between 1.9950 inches and 2.0050 inches

Mounting Lip Depth:

Between 0.0560 inches and 0.0660 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 353.0 and 358.0

Maximum Starting Torque:

1.00 inch-ounces

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

50.0 percent, rated amperes c and better finish

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

208.4 all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 2nd section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

2.5 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 3rd section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

75.0 single section

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0