

View Online at <https://aerobasegroup.com/nsn/5905-00-937-5419>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.735 inches

Body Diameter:

Between 1.609 inches and 1.641 inches

Shaft Diameter:

Between 0.247 inches and 0.249 inches

Shaft Length:

Between 0.859 inches and 0.891 inches

Mounting Bushing Length:

Between 0.359 inches and 0.391 inches

Body Length:

Between 0.830 inches and 0.840 inches

Overall Diameter:

Between 1.609 inches and 1.641 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

Between 0.526 inches and 0.536 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

1.0 kilohms single section

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Function Characteristic Per Section:

Single section linear

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0