## NSN 5905-00-937-7356

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-937-7356 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** Between 0.469 inches and 0.531 inches **Body Length:** Between 0.407 inches and 0.469 inches **Contact Arm Electrical Off Position:** Fully cw **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** Between 290.0 and 300.0 **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 100.0 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 290.0 and 300.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** U single section **Terminal Type And Quantity:** 3 eyelet Shelf Life:

N/a

## NSN 5905-00-937-7356

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0