## NSN 5905-00-937-9758

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-937-9758

Section Quantity:

**Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.047 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 0.484 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.492 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 percent, rated amperes c and better flooring **Power Dissipation Rating Per Section In Watts:** 2.0 7th secondary quality **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section

**Terminal Type And Quantity:** 3 tab, solder lug

## NSN 5905-00-937-9758

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0