Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-938-1309

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

2.707 inches

#### **Body Diameter:**

1.680 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

#### Shaft Length:

Between 1.203 inches and 1.297 inches

#### Mounting Bushing Length:

Between 0.453 inches and 0.547 inches

#### **Body Length:**

1.410 inches

#### **Overall Diameter:**

2.260 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Maximum Starting Torque:

40.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

#### Nonturn Device Location:

At 12 oclock

#### Nonturn Device Radius:

Between 0.485 inches and 0.515 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Locking bushing

# NSN 5905-00-938-1309

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Electrical Resistance Per Section:**

5.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

Between 275.0 and 305.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

25.0 heat sink single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

# Actuator Travel Control Feature:

#### Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

# Test Data Document:

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-22/3 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0