

View Online at <https://aerobasegroup.com/nsn/5905-00-938-3524>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.31150 inches and 1.31200 inches

Pilot Length:

Between 0.12700 inches and 0.13700 inches

Overall Length:

2.172 inches

Undercut Diameter:

Between 1.311 inches and 1.312 inches

Undercut Width:

0.07300 inches

Body Diameter:

1.453 inches

Shaft Diameter:

0.120 inches

Shaft Length:

0.672 inches

Body Length:

0.870 inches

Overall Diameter:

1.453 inches

Mounting Lip Diameter:

Between 1.43200 inches and 1.44200 inches

Mounting Lip Depth:

Between 0.08800 inches and 0.09800 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

0.70 inch-ounces

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00100 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.000 percent, rated amperes c and better finish

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 2nd section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0