NSN 5905-00-938-3526

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-938-3526 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.31150 inches and 1.31200 inches Pilot Length: Between 0.12700 inches and 0.13700 inches **Overall Length:** 1.542 inches **Undercut Diameter:** Between 1.311 inches and 1.312 inches **Undercut Width:** 0.07300 inches **Body Diameter:** 1.453 inches **Shaft Diameter:** 0.120 inches **Shaft Length:** 0.672 inches **Body Length:** 0.870 inches **Overall Diameter:** 1.453 inches **Mounting Lip Diameter:** Between 1.43200 inches and 1.44200 inches **Mounting Lip Depth:** Between 0.08800 inches and 0.09800 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 0.70 inch-ounces

Shaft Runout: 0.001 inches

NSN 5905-00-938-3526

A002a0

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00100 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.000 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
208.4 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.05/+0.05 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: