

View Online at <https://aerobasegroup.com/nsn/5905-00-938-4801>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.31150 inches and 1.31200 inches

Pilot Length:

Between 0.12700 inches and 0.13700 inches

Overall Length:

2.566 inches

Undercut Diameter:

1.315 inches

Undercut Width:

0.07300 inches

Body Diameter:

1.453 inches

Shaft Diameter:

0.125 inches

Shaft Length:

Between 0.734 inches and 0.766 inches

Body Length:

1.800 inches

Overall Diameter:

1.709 inches

Mounting Lip Diameter:

Between 1.43200 inches and 1.44200 inches

Mounting Lip Depth:

Between 0.08800 inches and 0.09800 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

0.70 inch-ounces

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00100 inches

Mechanical Backlash In Deg Angular Rotation:

0.041

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.10/+0.10 2nd section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 2nd section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections equation

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Test Data Document:

03538-7648736 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0