Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-938-5161

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

3.281 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.500 inches

#### Mounting Bushing Length:

0.250 inches

#### Body Length:

4.062 inches

#### Shaft Style:

Round, slotted

#### Shaft Bearing Type:

Bearing

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

9000.0

## Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# Mounting Method:

Standard bushing

# **Features Provided:**

Hermetically sealed

# **Electrical Resistance Per Section:**

1.0 ohms single section

# NSN 5905-00-938-5161

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

9000.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-2.0/+2.0 single section

**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

75.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0