NSN 5905-00-938-6423

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-938-6423 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.3115 inches and 1.3120 inches Pilot Length: Between 0.1270 inches and 0.1370 inches **Overall Length:** 2.172 inches **Undercut Diameter:** 1.312 inches **Undercut Width:** 0.0730 inches **Body Diameter:** Between 1.432 inches and 1.442 inches **Shaft Diameter:** 0.120 inches **Shaft Length:** 0.672 inches **Body Length:** 1.500 inches **Overall Diameter:** 1.627 inches **Mounting Lip Diameter:** 1.4370 inches **Mounting Lip Depth:** Between 0.0880 inches and 0.0960 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0

Maximum Starting Torque: 0.70 inch-ounces **Shaft Runout:**

0.001 inches

NSN 5905-00-938-6423

A002a0

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 kilohms all sections
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
230.0 all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.01/+0.01 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 all sections
Tap Location Tolerance Per Section:
-2.0/+2.0 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
8 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: