NSN 5905-00-939-4798

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-939-4798

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -25.0 to 25.0 Electrical Resistance: 1.000 kilohms Resistance Tolerance In Percent: -0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal cocument: 81349-milt-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Electrical Resistance: 1.000 kilohms Resistance Tolerance in Percent: -0.100 to 0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 0.126 inches and 2.282 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
1.000 kilohms Resistance Tolerance In Percent: -0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 0.342 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Resistance Tolerance In Percent: -0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Between 0.344 inches and 2.282 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Between 1.375 inches and 1.625 inches Body Diameter: Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Between 0.344 inches and 0.437 inches Body Length: Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Between 2.126 inches and 2.282 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document:
0.100 free air Style Designator: Axial terminal each end Test Data Document:
Style Designator: Axial terminal each end Test Data Document:
Axial terminal each end Test Data Document:
Test Data Document:
81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-10509/7 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: