## NSN 5905-00-940-2752

Film Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-00-940-2752  |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -100.0 to 100.0  |
| Electrical Resistance:   |
| 5.600 kilohms  |
| Resistance Tolerance In Percent:   |
| -2.000 to 2.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 150.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0 to 150.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Mil-std-1276 Wire Lead Type Designator:  |
|  |
| Reliability Indicator:   |
| Established  Division Filtra But All B |
| Reliability Failure Rate Level In Percent:   |
| 0.010  |
| Terminal Length:   |
| Between 1.000 inches and 1.625 inches  |
| Body Diameter:   |
| Between 0.098 inches and 0.161 inches  |
| Body Length:   |
| Between 0.260 inches and 0.450 inches  |
| Power Dissipation Rating In Watts:   |
| 0.500 free air   |
| Unpackaged Unit Weight:  |
| 0.75 grams   |
| Style Designator:  |
| Axial terminal each end Test Pote Posturant  |
| Test Data Document:  |
| 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification   |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain  |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  |
| Specification Data:  |
| 81349-mil-r-39017/2 government specification  Shelf Life:  |

--

N/a

**Unit Of Measure:** 

## NSN 5905-00-940-2752

Film Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0