NSN 5905-00-941-1447

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-941-1447 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.500 inches **Body Diameter:** 1.250 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.9375 inches **Mounting Bushing Length:** 0.4375 inches **Body Length:** 1.563 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 270.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 200.0 percent, rated amperes c and better finish **Rotary Actuator Travel In Angular Deg:**

270.0

Power Dissipation Rating Per Section In Watts:

Any acceptable

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

NSN 5905-00-941-1447

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0