NSN 5905-00-941-1757

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-941-1757 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.080 inches **Overall Height:** 0.330 inches **Overall Width:** Between 0.170 inches and 0.190 inches **Mounting Hole Diameter:** 0.087 inches **Shaft Diameter:** Between 0.090 inches and 0.150 inches **Shaft Length:** 0.070 inches **Body Length:** 1.010 inches **Body Width:** Between 0.170 inches and 0.190 inches **Body Height:** 0.330 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 4680.0 and 7200.0 **Lateral Distance Between Mounting Hole Centers:** Between 0.745 inches and 0.755 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end

Mounting Method: Unthreaded hole **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:**

Between 4680.0 and 7200.0

NSN 5905-00-941-1757

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0/+70.0 single section
Power Dissipation Rating Per Section In Watts:
0.7 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Derated to 45 pct of rated wattage at 125.0 degrees c
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No